



NuBroadlok Moisture Proof Latex Seam Sealer

DESCRIPTION

NuBroadlok Moisture Proof Latex Seam Sealer is recommended for seaming any moisture barrier backing offered by the Mohawk Group and all types of thermoplastic backed carpet products. Creates an impenetrable moisture barrier and offers perimeter protection when applied following our application guidelines. Engineered to exceed the British Spill and the 10,000 Impacts moisture testing protocols. Additionally, it prevents unraveling and/or delaminating of carpet backings and yarns.

NuBroadlok Moisture Proof Latex Seam Sealer can be used for direct glue, double stick and conventional stretch-in installations and is resistant to mildew, fungus and professional carpet cleaning.

FEATURES & BENEFITS

- Creates An Impenetrable Moisture Barrier
- CRI Green Label Plus Approved
- Non-Flammable
- Water Cleanup
- Low Odor/Odorless When Dry
- Suitable For Most Carpet Backings

PREPARATION

NuBroadlok Moisture Proof Latex Seam Sealer is not freeze/thaw stable. Do not allow the adhesive to freeze.

NuBroadlok Moisture Proof Latex Seam Sealer and substrate must be at least 65°F (18°C) or higher. Prepare and cut the carpet edges according to Mohawk Group's recommendations.

APPLICATION

Apply a 1/8" bead of adhesive to one side of the carpet along the backing edge where the face yarns enter the backing. Smooth out any excess adhesive being careful not to get any adhesive on the carpet nap.

Complete the seam by butting both sections of the carpet together while adhesive is still wet (5–10 minutes). If the carpet separates, realign both sections with a knee kicker to re-join the carpet edges.

To completely seal the installation, lift up the perimeter of the carpet and apply 1/4" bead around the perimeter of the room and all stationary objects. Lay the carpet so that the sealer makes contact with the wall or stationary object. When sealer is cured it will form an impervious barrier from topical moisture.

CLEAN UP

Do not allow adhesive to dry on carpet nap. Adhesive must be removed while it is still wet. Use a non-flammable cleaner to remove any traces of sealer left on the face of the yarn that can eventually attract dirt.



COVERAGE

NuBroadlok Moisture Proof Latex Seam Sealer 8 ounce (246.5 ML) container covers approximately 100 linear feet.

WARRANTY

Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Any implied warranty of merchantability of fitness for particular use is limited to one year from date of purchase. Liability for any incidental or consequential damage or loss is specifically excluded at all times. If used for other than professional purposes, any implied warranty of merchantability or fitness for particular use is excluded.

FIRST AID

In case of eye contact, flush with water for 15 minutes. Call a physician if irritation occurs. With skin contact, wash with soap and water. If swallowed, do not induce vomiting. Call a physician immediately. For more detailed information refer to the product material safety data sheet (MSDS).

HANDLING PRECAUTIONS

Protect from freezing.

Keep out of reach of children.

Please feel free to contact the Technical Services Department at 800.833.6954 for further information.